Attachment 3-21B Page 1 of 5

1

2

3

4

5

6

7

8

9

10

11

12

京の大大きの歌

· 本語、子品の は後

14

15

17

18

20

19

#1 #2

. . .

GARY B. JOHNSON, Continuing

EDWIN L. CARSTENSEN, Continuing

JONATHAN M. CHARRY, Continuing

ROBERT S. BANKS, Continuing

STAFF EXAMINATION

BY MR. FEBIGER:

Q. I'd like to begin with the material on the electrical effects of the AC-DC transmission lines. I'll be directing my questions to Mr. Johnson, who prepared the testimony on that subject.

I'd like to begin with the design information about the proposed and existing lines which you used for your analysis, Mr. Johnson. An overview of your information sources appears on Pages 8 and 9 of your testimony.

MS. LEWIS: Dr. Johnson; is a doctor.

MR. FEBIGER: Dr. Johnson; excuse me.

Q. You state that, in addition to information on cross-sectional configuration for the right of way, the petitioners provided you with line currents and ground clearances expected under heavy-power-load operating conditions. Is

that correct?

「おいかいからいってきるというは、おものできましていることできません。

1

2

3

5

7

8

9

10

11

12

13

14

15

16

17

18

19

20

2.1

22

23

2 4

- A. (Johnson) That's correct.
- Q. Does this statement mean that ground clearance is affected by the level of power load?
- A. (Johnson) It is affected by the power load. What happens, as you push more current through the conductors they warm up, and as they warm up they expand; and so sag a little bit, and get closer to the ground, as more and more power is transmitted over them.
- Q. I'd like to refer to Exhibits JB 1,

 JB 2 and JB 3 collectively. These are the crosssectional views of the right of way.

I note at the bottom of each of these figures or exhibits it indicates that the conductor sags and clearances are at 60 degrees Centigrade. Am I correct that this is air temperature?

- A. (Johnson) It's my understanding that 60 degrees Centigrade that you referred to would be the considerations of the air temperature; so it is a quite warm air temperature, very conservative assumption.
 - Q. In other words, it's a very high

worst-case temperature assumption?

を からい はなる からない できる かっちゅう

1

2

3

5

б

7

8

9

10

11

12

13

1.4

15

16

17

18

19

20

21

12

7)

4

- A. (Johnson) That's correct.
- Q. Would it reflect in any way the heating effect caused by the current that you referred to earlier?
- A. (Johnson) The exact assumptions that were used to determine that temperature, as given by the petitioners, I'm not certain of. I can check into that matter and get back to you on it.
- Q. On Page 9 of your testimony, you specified the assumption as to phase relationships of voltages on the AC conductors. Would you refer to the exhibits, and briefly explain the phasing assumptions that you made, and how you went about making them?
- A. (Johnson) Could you perhaps be a little more specific? Just in general terms, or?
- Q. In general terms, yes. What did you need to specify about the phasing?
- A. (Johnson) Well, in the case of AC lines, and the phasing of the different bundled conductors for a particular line, especially when you have say two AC lines together, you can choose the phasing. Depending on how you choose the

Attachment 3-21B Page 4 of 5

phasing, you will affect the electric fields let's say produced at ground level, and also the electric fields at the surface of the conductor.

Since the different conductors in the line are at different frequencies, they're at the same frequencies but at different phasings, so they will enhance or subtract from each other depending on how the phasings are chosen.

What I did was choose the phasings to produce the lowest electric field levels at ground level.

- Q. And that is the condition which would prevail most of the time, in your view?
 - A. (Johnson) Yes. That's my understanding.

MS. LEWIS: I don't believe I understood the question. What would prevail most of the time?

MR. FEBIGER: Well, the witness understood the question. He made some assumptions about phasing to use in calculating electrical effects on the edge of the right of way; and I'm just trying to determine if that's a condition which would prevail all of the time, most of the time...

1	
_	

2

3

MS. LEWIS: If that is the phasing that would always be present on the right of way? MR. FEBIGER: Yes.

Α.

6

5

7

8

9

10

11

12

13

14

15 16

17

18 19

20 21

22

23

24

(Johnson) In terms of the AC line, where the lines were existing, I used the existing phasings. For the new lines, I assumed a phasing that would give lower electric fields at ground If those are the phasings used, then they would be the phasings that would be used most of the time.

> Q. Thank you.

MR. FEBIGER: May I go off the record for a second?

> Sure. Off the record. MR. RAMM:

(Discussion off the record)

MS. RAMM: On the record.

BY MR. FEBIGER:

- Dr. Johnson, the cited reference for Q. your calculation of noise levels is indicated on Page 9. I'd like to refer to that. You used the Document Transmission Line Reference Book, 345 KV And Above, Second Edition; is that correct?
 - (Johnson) That's correct. Α.
 - Does this mean that the noise Q.